



Viking Proline II Series Aluminum

ISO 9001:2008 REGISTERED



Model	Inside Overall Length	Outside Overall Length	Install Weight (approx)	Water Level Capacity	10" Boards (optional)	Front Panel Height	Side Height	Tail-gate Height	Hoist	Conveyor Width
PL1011LW	10'	11'	4250 lbs	6.0 yd3	8.1 yd3	53"	38"	46"	20 ton	25"
PL1112LW	11'	12'	4400 lbs	6.6 yd3	9.0 yd3	53"	38"	46"	20 ton	25"
PL1314LW	13'	14'	4850 lbs	9.9 yd3	12.7 yd3	60"	45"	53"	30 ton	25"
PL1415LW	14'	15'	5000 lbs	10.7 yd3	13.8 yd3	60"	45"	53"	30 ton	25"
PL1617LW	16'	17'	5300 lbs	12.3 yd3	15.8 yd3	60"	45"	53"	35 ton	25"

Standard Features:

- 25:1 Planetary
- Double acting tailgate
- 1/2" UHMV poly wear plate under chain
- Front discharge
- Self-tension conveyor chain
- Body prop in rear hinge
- Aluminum alloy 5083 sides
- Right rear inspection ladder
- Air tailgate
- 3/8" box liner

Options:

- Rear discharge
- Reversible cross conveyors (chain or rubber)
- Front dual cross conveyor spinner (dual auger)
- Box lighting
- Material screens
- Air tarp
- Liquid tanks (up to 650 US gallons)
- High temperature box liners
- Hydraulic discharge gate

November 12, 2010



Viking-Cives (USA)
14331 Mill Street
Harrisville, NY 13648
315-543-2321 Phone
315-543-2366 Fax

Viking-Cives Ltd.
P.O. Box 1120 RR#4
Mount Forest, ON N0G 2L0
519-323-4433 Phone
519-323-4608 Fax

Viking-Cives Midwest
P.O. Box 295 22956 Hwy 61
Morley, MO 63767
573-262-3545 Phone
573-262-3540 Fax