



Viking Proline II LW Series

ISO 9001:2008 REGISTERED



Model	Inside Overall Length	Outside Overall Length	Install Weight (approx)	Water Level Capacity	10" Boards (optional)	Front Panel Height	Side Height	Tail-gate Height	Hoist	Conveyor Width
PL1011LW	10'	11'	5250 lbs	6.0 yd3	8.1 yd3	53"	38"	46"	20 ton	25"
PL1112LW	11'	12'	5450 lbs	6.6 yd3	9.0 yd3	53"	38"	46"	20 ton	25"
PL1314LW	13'	14'	6600 lbs	9.9 yd3	12.7 yd3	60"	45"	53"	30 ton	25"
PL1415LW	14'	15'	6800 lbs	10.7 yd3	13.8 yd3	60"	45"	53"	30 ton	25"
PL1617LW	16'	17'	7650 lbs	12.3 yd3	15.8 yd3	60"	45"	53"	35 ton	25"

Standard Features:

- 25:1 Planetary
- Double acting tailgate
- AR235 wear plate under chain
- Front discharge
- Self-tension conveyor chain
- Body prop in rear hinge
- 3/16" Corten-A steel in sides
- Right rear inspection ladder
- Air tailgate

Options:

- Rear discharge
- Reversible cross conveyors (chain or rubber)
- Front dual cross conveyor spinner (dual auger)
- High tensile construction
- Box lighting
- Material screens
- Air tarp
- Liquid tanks (up to 650 US gallons)
- Dupont Imron 5000 Paint
- Box liners
- Hydraulic discharge gate
- Stainless steel

November 12, 2010



Viking-Cives (USA)
 14331 Mill Street
 Harrisville, NY 13648
 315-543-2321 Phone
 315-543-2366 Fax

Viking-Cives Ltd.
 P.O. Box 1120 RR#4
 Mount Forest, ON N0G 2L0
 519-323-4433 Phone
 519-323-4608 Fax

Viking-Cives Midwest
 P.O. Box 295 22956 Hwy 61
 Morley, MO 63767
 573-262-3545 Phone
 573-262-3540 Fax