

FLEX PLOW

Trip Edge Reversible Snow Plows

Have the cast distance of a one way plow and the versatility of a reversible plow.

Enjoy complete plowing flexibility. You can always cast "Downwind".
Change the angle of your plow and send the snow wherever nature wants it.
It's as simple as that. Just pull the lever.

NOW FROM VIKING, YOU CAN HAVE IT BOTH WAYS



Shown in 14' Flex Plow with Parallel Lift

Simply angle the plow to the right and you have a right hand one-way plow , or angle to the left and you have a left hand one-way plow. Automatic contour using (2) 3" x 6 1/2" double acting hydraulic cylinders. Take these advantages and couple them with a proven trip edge design and a polymer moldboard and you are ready to tank on whatever winter offers!

PUSHFRAME OPTIONS:

- Twin cylinder power reverse with cushion valve
- Manual
- Parallel Lift

MOLDBOARD OPTIONS:

- Contour cylinders plumbed with power reverse
- Contour cylinders plumbed independently from power reverse
- Contour cylinders plumbed independently and separately

3" diameter x 6 1/2" stroke cylinders are moldboard contour.



SHOE OPTION:

- 12" Mushroom
- 10" Caster Wheels

SPECIFICATIONS

MODEL	PLOW LGTH	MOLDBOARD HGT NOSE / DISCHG.	CLEARING PATH	TRIP MECH.	MOLDBOARD MATERIAL	WEIGHT
R103250FL	10'	32" / 50"	8'-2" to 10'	(4) 7/8" dia. wire	3/8" UHMW polyethelene	2400 lbs.
R113151FL	11'	31" / 51"	9' to 11'	(5) 7/8" dia. wire	3/8" UHMW polyethelene	2500 lbs.
R123052FL	12'	30" / 52"	9' - 10' to 12'	(6) 7/8" dia. wire	3/8" UHMW polyethelene	2600 lbs.
R143052FL	14'	30" / 52"	11' 6" to 14'	(7) 7/8" dia. wire	3/8" UHMW polyethelene	2800 lbs.

*Backer angle is 4" x 4" x 3/4" material & the pushframe is ruggedly constructed of structural tubing with oscillating 1 1/4" thick push ears on either 21" or 30 1/2" centers.

*NOTE: Specifications are subject to change without notice. Use only VIKING authorized replacement parts and accessories to assure optimum performance and reliability.

Distributed By: